

STOCK RANGE OF PORTABLE TOOL TRANSFORMERS 1KVA TO 5KVA SINGLE PHASE & SPLITTER BOXES

Transformer tool ratings

- PT1000/2 1.0kVA with 2 x 110V 16A sockets.
- PT1500/2 1.5kVA with 2 x 110V 16A sockets.
- PT3300/2 3.3kVA with 2 x 110V 16A sockets.
- PT5000/3 5.0kVA with 2 x 110V 16A sockets
and 1 x 110V 32A socket.

Reference	20 minute tool rating	Continuous rating	Input connection	Weight
PT1000/2	1.0kVA	700VA	2m cable and 13A plug	11kg
PT1500/2	1.5kVA	1.0kVA	2m cable and 13A plug	11kg
PT3300/2	3.3kVA	1.5kVA	2m cable and 13A plug	17kg
PT5000/3	5.0kVA	2.2kVA	2m cable and 13A plug	29kg

Images are not to scale



PT 1500/2



PT 5000/3

Specification and construction

230~240V 50Hz input via 2m cable and 13 Amp UK plug.
110V output centre tapped to earth (55/0/55V).
To EN 61558-1: 2005 - CE marked.
Full thermal overload protection.
Output sockets to BS 4343: IP44.
High impact polyester/glass enclosures 1-5kVA.

4 way splitter box

To give 4 way multiple outputs from a single 110V 16 Amp transformer supply.

Output sockets to BS 4343.

Reference	Output sockets	Input connections	Weight
PTSB 4-2	4 x 110V 16 Amp	3m of arctic cable and 16 Amp 110V plug	2 kg



PTSB 4-2

