



STOCK RANGE OF IP23 ENCLOSED TRANSFORMERS FOR WALL OR FLOOR MOUNTING WITH 110V SOCKET OUTLETS

For 'hardwired' workshop applications to supply 110V power tools.

Stock (MV) range of single-phase (1ph) or two-wire (2ph) enclosed transformers with 110V centre tapped (55/0/55V) outputs.

Inputs 220~250V 1ph or 380~440V 2ph 50 / 60 Hz.

Enclosures to IP23 for wall or floor mounting.

Available with or without MCB output protection. MCBs mounted behind an IP65 accessible hinged cover.



WSP 3000/2 P2S1

A range of stock single-phase (1ph) or two-phase (2ph) enclosed multi-voltage (MV) transformers for workshop applications. The transformers within this range are enclosed in an EPN style IP23 enclosure with 110V centre tap to earth outputs. Output sockets are to BS EN 60309-1 (BS 4343) with 110V 16A or 110V 32A sockets fitted. Units are supplied with or without output socket MCB protection and input protection is via thermal overload on 220~250V versions or type D double pole MCB on 380~440V versions. All MCBs are mounted behind an IP65 hinged cover.

Reference	Input Voltages at 50 / 60 Hz + Input Protection	Transformer Rating (Continuous or 20 minute Tool Rated)	Sockets	Enclosure Reference + Dimensions L x W X H (mm)	Output Protection (DP Type D)	Weight (kg)
WS 3000/2 P1S1	220/230/240/250V Thermal overload	1.5kVA continuous or 3.0kVA tool rated	2 x 110V 16A	EPN 5 350 x 242 x 353	None	18
WS 4000/3 P1S1	220/230/240/250V Thermal overload	2.0kVA continuous or 4.0kVA tool rated	3 x 110V 16A	EPN 5 350 x 242 x 353	None	22
WS 5000/2 P1S1	220/230/240/250V Thermal overload	2.5kVA continuous or 5.0kVA tool rated	1 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	None	28
WS 6000/3 P1S1	220/230/240/250V Thermal overload	3.0kVA continuous or 6.0kVA tool rated	2 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	None	32
WSP 3000/2 P1S1	220/230/240/250V Thermal overload	1.5kVA continuous or 3.0kVA tool rated	2 x 110V 16A	EPN 5 350 x 242 x 353	1 x 16A	18
WSP 4000/3 P1S1	220/230/240/250V Thermal overload	2.0kVA continuous or 4.0kVA tool rated	3 x 110V 16A	EPN 5 350 x 242 x 353	1 x 16A 1 x 32A	22
WSP 5000/2 P1S1	220/230/240/250V Thermal overload	2.5kVA continuous or 5.0kVA tool rated	1 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	1 x 16A 1 x 32A	28
WSP 6000/3 P1S1	220/230/240/250V Thermal overload	3.0kVA continuous or 6.0kVA tool rated	2 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	1 x 16A 1 x 32A	32

Reference	Input Voltages at 50 / 60 Hz + Input Protection	Transformer Rating (Continuous or 20 minute Tool Rated)	Sockets	Enclosure Reference + Dimensions L x W X H (mm)	Output Protection (DP Type D)	Weight (kg)
WS 3000/2 P2S1	380/400/420/440V 20A DP MCB	1.5kVA continuous or 3.0kVA tool rated	2 x 110V 16A	EPN 5 350 x 242 x 353	None	18
WS 4000/3 P2S1	380/400/420/440V 25A DP MCB	2.0kVA continuous or 4.0kVA tool rated	3 x 110V 16A	EPN 5 350 x 242 x 353	None	22
WS 5000/2 P2S1	380/400/420/440V 32A DP MCB	2.5kVA continuous or 5.0kVA tool rated	1 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	None	28
WS 6000/3 P2S1	380/400/420/440V 40A DP MCB	3.0kVA continuous or 6.0kVA tool rated	2 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	None	32
WSP 3000/2 P2S1	380/400/420/440V 20A DP MCB	1.5kVA continuous or 3.0kVA tool rated	2 x 110V 16A	EPN 5 350 x 242 x 353	1 x 16A	18
WSP 4000/3 P2S1	380/400/420/440V 25A DP MCB	2.0kVA continuous or 4.0kVA tool rated	3 x 110V 16A	EPN 5 350 x 242 x 353	1 x 16A 1 x 32A	22
WSP 5000/2 P2S1	380/400/420/440V 32A DP MCB	2.5kVA continuous or 5.0kVA tool rated	1 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	1 x 16A 1 x 32A	28
WSP 6000/3 P2S1	380/400/420/440V 40A DP MCB	3.0kVA continuous or 6.0kVA tool rated	2 x 110V 16A 1 x 110V 32A	EPN 6 384 x 305 x 454	1 x 16A 1 x 32A	32

Eastern Transformers and Equipment Ltd

Tel: 01284 388 033

Fax: 01284 386 969

info@ete.co.uk / sales@ete.co.uk

www.ete.co.uk