

## STOCK RANGE OF ENCLOSURES IN RAL 7035 GREY WITH OPAQUE DOORS TO IP65

IP65 enclosures with opaque doors.

Rated voltage up to 690V and maximum current of 800A

Made from HB ABS halogen-free material.

IP65 protection rating against solid objects and liquids.

IK08 degree of protection against mechanical impacts.

CE and RoHs marked.



PP3001

The PP range of IP65 enclosures with opaque doors in various sizes. The enclosures in this series have a rated voltage up to 690V and are resistant to chemical agents, alkalis, oils, and salts. The maximum current of the units is 800A and they possess an operating temperature or between  $-35^{\circ}\text{C}$  and  $+65^{\circ}\text{C}$ . They are made from HB ABS halogen-free material and are mounted on a 1 mm galvanised steel mounting plate. All models are IP65 protected against solid objects and liquids and IK08 protected against mechanical impacts. The standard colour of the units is RAL 7035 (grey) with other colours available upon request. All types are CE and RoHs marked and available from stock.

Reference	Colour	Dimensions D x W x H (mm)	Weight (kg)
PP3001	RAL 7035 (grey)	130 x 200 x 300	1.80
PP3002	RAL 7035 (grey)	150 x 250 x 350	2.40
PP3004	RAL 7035 (grey)	170 x 300 x 400	3.00
PP3005	RAL 7035 (grey)	220 x 300 x 400	3.40
PP3006	RAL 7035 (grey)	190 x 350 x 500	4.35
PP3003	RAL 7035 (grey)	175 x 400 x 500	4.50
PP3007	RAL 7035 (grey)	240 x 400 x 500	5.40
PP3008	RAL 7035 (grey)	200 x 400 x 600	5.85
PP3010	RAL 7035 (grey)	250 x 500 x 700	9.70
PP3021	RAL 7035 (grey)	260 x 600 x 800	10.80