

Comprehensive range of Plastim stock enclosures all rated to IK08 & IP65 with a polyurethane sealing gasket.

The PP range of enclosures are all CE RoHS certified.

Available in RAL7035 Grey.

Made from HB ABS with a 1mm galvanised steel mounting plate.

Operating temperature ranges from -35°C to +65°C.

Maximum rated current of up to 800A and a maximum rated voltage of up to 690V.

The PP range of enclosures are all resistant to chemical agents, alkalis, oils, salts, etc.

The range are available in 4 different variants:

- Grey with opaque grey door.
- Grey with transparent door.
- Modular grey enclosure with opaque door.
- Modular grey enclosure with transparent door.



PP3008



PP3014

A comprehensive range of IK08 & IP65 Enclosures.
Complete with a wide range of sizes and 4 different variants.

Grey enclosure with opaque door.

Reference	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
PP3001	200	300	130	1.7
PP3002	250	350	150	2.2
PP3003	400	500	175	4.3
PP3004	300	400	170	3.0
PP3005	300	400	220	3.4
PP3006	350	500	190	4.3
PP3007	400	500	240	5.6
PP3008	400	600	200	6
PP3010	500	700	250	10.1
PP3021	600	800	260	13.5

Grey enclosure with transparent door.

Reference	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
PP3011	200	300	130	1.7
PP3012	250	350	150	2.2
PP3013	400	500	175	4.3
PP3014	300	400	170	3.0
PP3015	300	400	220	3.4
PP3016	350	500	190	4.3
PP3017	400	500	240	5.6
PP3018	400	600	200	6.0
PP3020	500	700	250	10.1
PP3022	600	800	260	13.5

Grey modular enclosure with opaque door.

Reference	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
PP3102	250	350	150	2.5
PP3104	300	400	170	3.4
PP3106	350	500	190	4.5
PP3108	400	600	200	6.0

Grey modular enclosure with transparent door.

Reference	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
PP3102	250	350	150	2.5
PP3104	300	400	170	3.4
PP3106	350	500	190	4.5
PP3108	400	600	200	6.0